



Ecoglo "Pictogram Left" S20 Signs are designed to be used in and about buildings to identify escape routes to meet NZBC Clause F8 "Signs". The signs will be clearly visible and readily understandable under all conditions of foreseeable use, including emergency conditions.

SIGN DEFINITION

Exit left from here.

COMPLIANCE

Ecoglo "Pictogram Left" S20 signs can be used to meet F8/AS1, as detailed below, or can be used in alternative solutions. Phone Ecoglo or email Engineer@ecoglo.com for design advice for alternative solutions.

PERFORMANCE

Risk Group C Building

30 minutes visibility

Minimum charging illuminance of 100 lux continuously during occupancy will ensure minimum luminance of 30 mcd for 30 minutes after failure of the main lighting.

Risk Group B Building

90 minutes visibility

Minimum charging illuminance of 350 lux continuously during occupancy will ensure minimum luminance of 30 mcd for 90 minutes after failure of the main lighting.

UV Resistance - Loss of luminance after 1000 hrs ASTM G-155 Cycle 1 exposure: <10%: Pass

Salt Spray Resistance - ASTM B117: Pass

Washability - ASTM D4828: Pass

Rate of Burning - ASTM D635: Pass

Surface Flammability - ASTM E162: Pass

Toxicity - Bombardier Toxic Gas Generation Test SMP800-C: Pass

Radioactivity - ASTM D3648: Pass

SUPPLY

The products are available in 2 sizes - maximum viewing distance 16 metres and maximum viewing distance 24 metres. Double sided versions are also available in the 2 sizes.

PRODUCT CODE	PRODUCT NAME	SIGN DEFINITION	SIGN SIZE	MAXIMUM VIEWING DISTANCE
S20-RML2916-16m	Pictogram Left	Exit left from here	290mm x 162mm	16 metres
S20-RML4223-24m	Pictogram Left	Exit left from here	420mm x 230mm	24 metres
DSS20-RMD2916-16m	Pictogram Double Sided	Exit left or right from intersection	290mm x 162mm	16 metres
DSS20-RMD4223-24m	Pictogram Double Sided	Exit left or right from intersection	420mm x 230mm	24 metres

COMPOSITION

The high visibility flat panel is manufactured from 5005 0.9mm aluminium sheet. Custom made photoluminescent pigments are embedded in thermoset polyester carriers to integrally bond the active ingredients onto the aluminium sheet following curing at high temperature.

INSTALLATION

The standard sign is supplied with fixers for mounting flat on a wall.

Mounting brackets are available for ceiling and wall fixing.

Mounting brackets take one sign or two signs back to back.

PRODUCT CODE	PRODUCT NAME	CEILING MOUNT BRACKET	WALL MOUNT BRACKET
S20-RML2916-16m	Pictogram Left	B1-290	B1-162
S20-RML4223-24m	Pictogram Left	B1-420	B1-230
DSS20-RMD2916-16m	Pictogram Double Sided	B1-290	B1-162
DSS20-RMD4223-24m	Pictogram Double Sided	B1-420	B1-230

Contact

Ecoglo International Limited

77 Kingsley St, Sydenham 8023

PO Box 7698, Sydenham 8240, Christchurch, New Zealand

Phone: 03 348 3781 **Fax:** 03 343 6821

Email: info@ecoglo.com **Web:** www.ecoglo.co.nz